

Serijet SJ

Screen Inks

SERICOL

Product

Information

Serijet SJ is fast drying Satin finish solvent-based ink for uncoated paper and board

Main Characteristics

Finish	Drying	Thinning & Wash-up	Mesh	Stencil Type	Coverage & Mesh No.	Applications	Colour Range
Satin / Matt	Air / Jet	10-20% Thinner #1 or Mineral Turps. Hot shop conditions use Slow Thinner #2 High speed printing use Fast Thinner #3 Wash up with Universal Washup #1	77.48 – 120.34 monofilament	All solvent resistant films and emulsions are suitable Recommended emulsions: Dirasol 915 Dirasol 916	60-75 m ² /kg may be expected using a 100.48 mesh.	Uncoated paper and board. Posters, Hardboard, Showcards, Wood, Polystyrene, Wallpapers, Fibreboard,	15 standard colours, plus process set, Black, White, process colours and Toning medium

Properties

Fast Drying for ease of use. Excellent coverage and hold-out on absorbent stocks. Satin Finish for optimum appearance on paper and board.

IMPORTANT: Stir well before every use. Some colours contain lead chrome pigments and are not suitable for toys or articles likely to be sucked or chewed by children.

Exterior Use

Paper and board substrates are typically not suitable for long-life exterior applications.

Drying

Serijet SJ will jet dry in 10-15 secs at a setting of 70°C, or air dry in 5 to 15 minutes depending upon conditions.

Safety and Handling

- Products marked (T) contain lead and should not be used on objects likely to be sucked or chewed by children, and may cause harm to the unborn child
- All other products are formulated free of lead and other heavy metals

Comprehensive information on the safety and handling of Serijet SJ screen inks and thinners is given in the appropriate Sericol Material Safety Data Sheets (MSDS), which are available on the Sericol Product Catalogue CD or upon request.

The MSDS should be consulted before handling any inks or chemicals.

Environmental Information

Serijet SJ:

- Does not contain ozone-depleting chemicals as described in the Montreal convention

Standard Colours

857201	Serijet SJ Black	857101
857202	Serijet SJ White	857102
857203	Serijet SJ EL Brilliant Yellow	857103
857204	Serijet SJ Basic Yellow (T)	
857205	Serijet SJ Golden Yellow (T)	
857206	Serijet SJ Orange (T)	
857207	Serijet SJ Warm Red (T)	
857208	Serijet SJ EL Brilliant Red	
857209	Serijet SJ Waratah	
857210	Serijet SJ Rubine	
857211	Serijet SJ Rhodamine	
857212	Serijet SJ Purple	857121
* 857213	Serijet SJ Violet	
857214	Serijet SJ Reflex Blue	
857215	Serijet SJ Basic Blue	
857216	Serijet SJ Basic Green	
022161	Serijet SJ Ultra Blue	
857200	Serijet SJ Extender	
** 022191	Serijet SJ Metallic Medium	
Process Colours		
** 857217	Serijet SJ EL Process Yellow (T)	
857218	Serijet SJ EL Process Magenta	
857219	Serijet SJ EL Process Cyan	
** 857463	Serigraph SG / Serijet SJ Tone Medium	

Available in 4kg packs

* Available in 1kg pack only

** Available in 3.8kg pack only

(T) = Lead containing

Thinners

Thinner #1
Slow Thinner #2
Fast Thinner #3

Thinners available in 5L and 20L packs

Wash up

Universal Washup #1

Available in 20L pack

Special Matches

Matches can be supplied against prints, wet samples, or colour references such as PANTONE™. A sample of the substrate to be printed, the mesh to be used, as well as any other relevant information should be attached to the order.

Minimum quantity 1kg

Storage

- Tins should be kept tightly closed when not in use.
- Stir well before each use

The information and recommendations contained in this Product Information sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on our present knowledge and believed to be accurate. However, no guarantee regarding their accuracy is given as we cannot cover or anticipate every possible application of our products and because manufacturing methods, printing stocks and other materials vary. For the same reason our products are sold without warranty and on condition that users shall make their own tests to satisfy themselves that they will fully meet their particular requirements. Our policy of continuous product improvement might make some of the information contained in this Product information sheet out of date and users are requested to ensure that they follow current recommendations.

SERICOL
More than ink... Solutions.

FUJIFILM Sericol Australia Pty Limited, 4 Coronation Ave, Kings Park, NSW 2148
Telephone: (02) 8825 2700 Fax: (02) 9621 8100

Technical Helpline : 1300 135 357 Orders Hotline : 1300 650 504